

Vinyl and Faux Leather Fabrics

teal

Manufacturer:

Spradling®

Fabric Range:

Avantgarde™

Description:

Avantgarde™ is Spradling®'s most premium faux leather collection. With its soft touch and delicate leather-like fine grain, your upholstered surfaces will make the difference. Avantgarde™ offers you the ultimate solution for surface protection against virus bacteria, stains, and abrasion, meeting the highest flame resistance norms in the contract market. With Permablok3® Plus, Avantgarde™ will make your upholstered surfaces easier to clean, significantly improving the removal of stains and dye-transfer. Available in 20 colourways.

Design Style:

Colour Selections:

AMBER | AVA-0015

ANGORA | AVA-0003

ATLANTIC | AVA-0019

BRULÉE | AVA-0004

CERAMIC | AVA-0022

CHROME | AVA-0023

CITRONELLE | AVA-0014

CLEMENTINE | AVA-0016

CONCRETE | AVA-0024

ECLIPSE | AVA-0021

INCENSE | AVA-0005

KETCHUP | AVA-0013

MIDNIGHT | AVA-0025

ORCHIDEA | AVA-0010

PETROL | AVA-0020

PRISTINE | AVA-0002

ROSEWOOD | AVA-0008

SAUVIGNON | AVA-0012

SCARLET | AVA-0017

WALNUT | AVA-0001

Composition:

Topcoat: Vinyl
Backing: 100% Cotton

FR Certification: :

AT ÖNORM B 3825, Gruppe I	INT IMO 2010 FTP Part 8
AT ÖNORM A 3800 Teil I	INT IMO 2010 FTP Part 5
DE DIN 4102 B2	IT UNI 9175 Classe 1.1M
EU EN 1021 Part 1 & 2	US FMVSS302
EU EN 71-2:2006+A1:2007	US CAL TB 117-2013
Safety of Toys - part 2.	US FAR 25/853
FR NF P 92-503 / M1	US NFPA 260 - Class I
FR NF D 60-013 (art. AM I8)	US UFAC Fabric Class I
GB BS 5852 Part 2 CRIB 5	
GB BS 5852 Part 2 CRIB 7	

Fabric care and maintenance:

IMPROVED DYE RESISTANCE AND CLEANING

PERMABLOK3® PLUS+ from SPRADLING® is a newly developed protective coating combining the well-known and proven PERMABLOK3® formula (anti-bacterial and anti-abrasion) with an enhanced resistance to stains: it seals the surface providing a shield against stains, makes cleaning easier and improves removal of dye-transfer*.

*Removal of stains and indigo dye may vary depending on the type of textile, time of exposure, surrounding conditions, cleaning and maintenance of the material. PERMABLOK3® PLUS+ offers improved protection to indigo dye and stains, yet full removal or cleaning cannot be guaranteed. Please read our cleaning and maintenance guide carefully to achieve best results.

CARE AND CLEANING GUIDE

The vinyl should be cleaned periodically in order to maintain its appearance and prevent build-up of dirt and contaminants.

Any stain, spills, or soiling should be cleaned up promptly to prevent the possibility of permanent staining.

Use soft soapy solutions or special cleaning products for vinyl fabrics to remove stains on the surface of the material. Remove only with a damp white cloth.

Lacquers, strong cleaners, detergents, xylene-based solutions, acetone, or ketone (MEK) cause immediate damage and contribute to the deterioration of the material. The use of such cleaners is at the owner's risk.

DAILY CLEANING AND MAINTENANCE

1. Clean the entire surface using a mixture of 1:9 liquid soap (neutral pH) and water. Do not use soap or cleaning solutions that contain alcohol, ketones, xylene, acetates or solvents (mineral/white spirits).

2. Completely remove excess cleaner with a white, clean, damp cloth.

3. Dry the surface.

GET RID OF STAINS WITH ONE OF THE FOLLOWING METHODS

METHOD 1

Coffee, juice, red, wine, sauces, chocolate, grease, crayon and suntan lotion.

Care and Cleaning Process

Remove excess spill with a damp, white cloth or soft brush. Clean with a 1:9 mix of liquid neutral PH soap and water. Next, rinse with clean water and dry.

METHOD 2

Make-up

Care and Cleaning Process

Use a straight application of neutral PH soap. Wipe with a clean white cloth or soft brush, rinse with clean water, and dry.

METHOD 3

Blood, urine, feces

Care and Cleaning Process

Use a 1:1 mix of Isopropyl alcohol and water. Rinse with clean water and dry.

METHOD 4

All other tough stains

Care and Cleaning Process

Use a 0,5% solution of household bleach and water (1:9 mix of 5% concentrated household bleach and water). Rinse thoroughly with clean water and pat surface dry.